Phone: 760.929.8559 • 1.800.634.8537 • Fax: 760.929.1901 • www.standardfilter.com 5928 Balfour Court • Carlsbad, California 92008

Hardware

Clamps



Clamp Number	<u>Minimum</u>	<u>Maximum</u>	
500-072	2.0000	5.0000	
500-104	1.7500	7.0000	
500-128	1.7500	8.5625	
500-152	2.0000	10.0000	
500-188	2.0625	12.3125	
620-390	22.8750	24.8750	

With Standard Filter's Snap-Lock clamps, installation time is reduced considerably over that of traditional worm gear clamps. Simply insert the band, pull tight, lock and with 2-3 turns of the screwdriver you're set. The clamp features a 1/2" 301 stainless steel band, 410 stainless steel bridge and a 5/16" hexhead.screw Clamps are used on raw edge top bags or cord bottom bags fitted to a thimble. Additional sizes available upon request.

Eye Bolt Caps

Replacement caps for reverse-air baghouses are available from Standard Filter . We carry various sizes from 5" diameter through 12" diameter in both 18 gauge and 20 gauge carbon steel. Eye bolt configurations can be made opened or closed to match your bag hanging hardware. We can also supply stainless steel and galvanized caps for areas where corrosion is present.

Hangers

Standard Filter provides a variety of different types of hangers; single loop, double loop and coined loop just to name a few. Hangers are constructed of 3/16" diameter wire and available in both carbon and stainless steel.





Venturis

Venturis add to the cleaning efficiency of pulse-jet baghouses. Standard Filter offers a wide variety of styles and sizes for both top and bottom removal cages. We can supply either spun or cast venturis manufactured from carbon steel, stainless steel, aluminum or galvanized.

Sonitec™ 2000 Nozzles

Also available from Standard Filter is an alternate to venturis:
The Sonitec[™] 2000 Nozzle. These may be used for new and retrofit installations.
No more venturis means a larger flow area and less pressure drop without sacrificing cleaning efficienthe concentrated air blast from the Sonitec[™]
2000 provides cleaning action for bags up to 20 feet in length. Sonitec[™]
Nozzles screw directly into the blow-pipe and never need replacing.
Available in brass and stainless steel.

Phone: 760.929.8559 • 1.800.634.8537 • Fax: 760.929.1901 • www.standardfilter.com 5928 Balfour Court • Carlsbad, California 92008

Hardware

Gauges

*Single diaphragm



Part No.	<u>Range</u>	Part No.	<u>Range</u>
2010	0-10	A3010	0-10
2015	0-15	A3015	0-15
2020	0-20	A3020	0-20

The listed part numbers are the most commonly used items .

Diaphram Valves / Pilot Solenoid Valves

+Double diaphragms

Diaphragm and solenoid valves work together for efficient operation of the baghouse cleaning systems.

Diaphragm Valve Model		(CA or RCA)	Pilot Solenoid Valves	
Pipe Size	Model	Repair Kit	Pipe Size	Model
3/4"	20T, DD*	K2000	1/8/M3 NPT	RCA3D2T
1"	25T, DD , MM	K2501	1/8/M6 PUSH	RCA3P
1 1/2"	35T*	K3500		
1 1/2"	40 MM	K4000	Multi Valve Enclosures	
1 1/2"	45T2, DD2+	K4502	Description	Model
2"	50T+	K5004	5 Valve Encl.	RCA3-5V2,3,4,5
2 1/2"	62T+	K5004	8 Valve Encl.	RCA3-8V6,7,8
3″	72T, MM	K7600	12 Valve Encl.	RCA3-12V9,10,11,12

Available in AC/DC

